

ZAC® Anchors

3/8" HWH termination fastener  
For fastening termination bar at wall terminations



- Term bar fastener that can be backed out.
- Threads into wood, masonry, concrete and metal.
- ZAC cap is zinc aluminum composition and will never red rust.

- Can be removed and re-engaged for roof repairs without damage to the roof system.
- Standard black e-coat coating on thread.

Application

ZAC Anchor

Use with:  
Wood, masonry, concrete,  
and steel at roof wall terminations.



Head: 3/8" AF ZAC HWH Long Life  
Dia: #14 (.248)

Notes

Dimensions are nominal and in inches unless noted.

Performance Load Capacities (2000 psi concrete)

Pre-Drill	7/32"	7/32"	7/32"	7/32"
Embed. Depth	1"	1.25"	1.375"	1.5"
Tension Load (lbs)	620	810	905	1000
Shear Load (lbs)	830	1130	1280	1430

Notes: All load values listed are ultimate load capacities and are not allowable load capacities. These loads should be reduced by an appropriate safety factor of at least 4 to determine the allowable load.

Selection

Dia and Length	Part No.	Carton Wt. (lbs)	Carton Qty.	Skid Qty.
#14 x 1-3/8" HWH ZAC Anchor	N7305-FM999C	25	1000	60,000


Notes: Load capacity is related to embedment depth. Select anchor length to provide needed embedment depth for the installed anchor.

Installation

Tools: Carbide-tipped masonry drill bit sized slightly larger than nominal diameter to allow clearance.

Options

Termination Product



Coatings

