




**Blue
MAX**

THE LOG FASTENERS WITH MAXIMUM GRIP

**With Torque
Reducing Wings**

Blue Max Features and Benefits:

- Self-drilling, fast, and easy to install—no pilot pre-drilling required, saves time and money
- Hex Head ensures secure non-slip engagement—user friendly and simple to insert
- Large built-in washer guards against overdriving—assures proper setting depths and provides added pulldown strength for warped logs
- Chamfered underhead allows countersinking—eliminates added steps with lag screws
- Unique wing design reduces drilling torque and allows natural log settlement (lengths 8"–15")—reduces equipment costs, eliminates installation failures
- Heat treated steel provides maximum pull down, shear and tensile strengths—heat treating improves structural properties and part reliability
- Exclusive Blue E-Coat corrosion resistant coating outperforms other finishes—exceeds Factory Mutual Corrosion-Resistance Standard 4470
- Waxed parts speed installation, reduces drilling torque, and improves drill life
- Packaged in durable plastic pails—protects parts from weather, can be stored on site, and comes with easy carrying handle
- Trusted engineering data based on ICC Evaluation Service ESR 1876—assures maximum performance based upon independent evaluation
- Free magnetic driver bit with every pail—no additional expenses, installation begins immediately, magnetic bit secures fastener insertion for higher efficiency
- Free heavy duty washers with every pail—greatly enhances pulldown power for warped and twisted logs
- Oversized thread provides increased strip-out resistance and high pull-out strength so that logs stay securely locked together
- Rico point for light gauge steel penetration (if applicable)
- 3" thread length—maximum pullout resistance when compared to the competition

Head Type: 5/16" Hex Head
Thread Diameter: 0.317"
Shank Diameter: 0.230"

Thread Length: 3"
T.P.I.: 7.5
Point Type: Rico

For complete engineering data, see ICC-ESR1876 at www.icc-es.org

Length	Part Number	Carton Wt. (lbs)	Carton Qty.	Skid Qty.
6"	B6648-932F	21	250	15,000
8"	B6664-932F	26	250	15,000
9"	B6672-932F	29	250	10,000
10"	B6680-932F	32	250	10,000
11"	B6688-932F	35	250	10,000
12"	B6696-932F	38	250	10,000
14"	B6712-932F	44	250	10,000
15"	B6720-932F	47	250	10,000

Installation Instructions:
 Use 1/2" high torque, low speed drill (0–1000 RPM) with 5/16" hex driver. Allow for minimum 3" penetration into the bottom log with 1/4" countersink depth. Always consult your engineer for proper placement procedures.

Technical advice and sales service

SFS intec, Inc.
 FasteningSystems
 Spring St. & Van Reed Rd.
 P.O. Box 6326
 Wyomissing, PA 19610

800 234 4533
 T 610 376 5751
 F 610 376 8551
www.sfsintecusa.com

SFS intec

Turn ideas into reality.